

Lancaster Clear-Flow

"Point Of Use" Filters



Features

Available in both Activated Carbon or Sediment Removal, these Clear-Flow water filter cartridges have been designed for potable water filtration applications to afford you cleaner, clearer, better-tasting water.

- Activated Carbon Cartridges**
 will remove objectionable chlorine, foreign tastes, odors and most colors.
- Sediment Filter Cartridges**
 will trap sand, dirt, silt, algae and most visible suspended material.

SEDIMENT		
Filter Model #	200	210
Cartridge #	20	21
Cartridge Dimension	2-3/4" x 9-3/4"	2-3/4" x 19-7/8"
G.P.M.	1-10	1-20
Micron	15	15

CARBON		
Filter Model #	400	410
Cartridge #	40	41
Cartridge Dimension	2-3/4" x 9-3/4"	2-3/4" x 19-7/8"
G.P.M.	1-10	1-20
Micron	10	10

LWTUS Twin Filter System

The LWTUS Twin Filter System comes complete with NSF-approved quick-connect fittings, self-piercing feed valve, NSF-approved tubing, and long-reach chrome faucet.* The standard system also comes with a #20C sediment filter cartridge and a #40 activated carbon cartridge. Custom filter configurations are available, see chart below.

MODEL#	TYPE	FILTER SIZE	CONTAMINANTS
7-LWTUS-1C (STANDARD)	SEDIMENT, CARBON	2.5" x 10"	TASTE, ODOR, CHLORINE
7-LWTUS-1N	SEDIMENT, NITRATE	2.5" x 10"	NITRATES
7-LWTUS-1KDF85	SEDIMENT, KDF	2.5" x 10"	HYDROGEN SULFIDE
7-LWTUS-1A	SEDIMENT, ARSENIC	2.5" x 10"	ARSENIC
7-LWTUS-1CBC	SEDIMENT, CARBON BRIQUETTE	2.5" x 10"	GIARDIA, CRYPTOSPORIDIUM, ENTAMOEBIA, TOXOPLASMA CYSTS
7-LWTUS-1F	SEDIMENT, FLUORIDE	2.5" x 10"	FLUORIDE



*Designer Faucets Also Available In Oil-Rubbed Bronze Or Brushed Nickel At Additional Charge