

# LANCASTER®

## WATER TREATMENT

Lancaster's Sediment Filters will remove dirt, silica and most suspended matter from your water supply down to a 20 micron filtering level!

Utilizing the mineral *Filter Ag*, these units require no chemical regenerent - just a simple, periodic backwash is all that is needed to maintain optimum performance.

When using this filter, it should be placed first in line before any other filter or softener, if suspended matter could interfere with the performance of your equipment.

Designed with top mounted Fleck controls and non-corrosive, fiberglass mineral tanks, *Lancaster Sediment Filters* are sure to satisfy your every need.

## SEDIMENT FILTERS



E-AUTOMATIC



M-MANUAL

SEDIMENT FILTERS WITH FILTER AG SPECIFICATIONS					
MODEL NUMBER	TYPE	VALVE - 1"	TANK	SERVICE GPM	BKWSH GPM
7-MST-1	Manual	1500M - 3/4"	10 x 44	5	5
7-MST-2			12 x 48	7	7
7-EST-1	Electric	5610F	10 x 44	5	5
7-EST-2			12 x 48	7	7
7-EST-3		2750F	14 x 65	11	10
7-EDBST-1	Electric with Dome Hole and Bottom Drain	5610F	10 x 47	5	5
7-EDBST-2			12 x 48	7	7

Maximum Operating Pressure: 125 PSI

Maximum Operating Temperature: 120° F